NOTES:		115101-05-XX.XX	REVISIONS			
1. PACKAGE CABLE ASSEMBLIES IN A BAG. LABEL BAG WITH AMPHENOL 115101-05-XX.XX	ΔΝΠ ΠΔΤΕ ΓΩΠΕ	DRAWING NO.	REV	DESCRIPTION	DATE	ECO APPR
2. CABLE ASSEMBLY TO BE 100% TESTED FOR HI POT, CONTINUITY, SHORTS AND OPEN.		THIRD ANGLE PROJ. 🕀 🗧	A	RELEASE TO MFG.	18-May-10	[[]
Z. CABLE ASSEMBLT TO BE 100 % TESTED FOR HT POT, CONTINUTT, SHORTS AND OPEN.					SCALE 0.750	
	LENGTH XX.X	(X (SEE TABLE) —				
TYP (2) (1) TYP (2) (2) (2) (2) (2) (2) (2) (2) (2) (2) (2)	LENGTH PART NUMBER 115101-05-06.00 115101-05-12.00 115101-05-24.00 115101-05-36.00 * ADDITIONAL LENGTI BY CHANGING XX.X CONTACT CONNEX N	LENGTH (IN.) 06.00 ± 0.25 12.00 ± 0.25 24.00 ± 0.50 36.00 ± 0.50			(3) TYP (2)	
DESIGN REQUIREMENTS: FREQUENCY: TO GHz X CONTINUITY VSWR: 1 MAX X HI-POT :1000 VRM	15		009-954-341	A/R 3 A/R 2	HEAT SHRINK TUBE RG 179 CO-AXIAL CABLE	BLACK
INS. LOSS dB MAX			112954 PART NUMBER		RUE 75 OHM BNC CRIMP PLUG DESCRIPTION	FINISH
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES $\pm .015$ (0,381 mm) $\pm .005$ (0,127 mm) $\pm 1^{\circ}$ NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. MATERIAL	CLE ENC CLE APF	MENT 18-M GINEER DATI	ay-10 TRUE TRUE ay-10 USING	75 OHM BNC CRIMF 75 OHM BNC CRIMF , RG 179 CABLE, US LENGTHS	PLUG TO Amnh	enol nex