



Specification Status: Released

BENEFITS

- ESD protection for high frequency applications
- Smaller form factor for board space savings
- Helps protect electronic circuits against damage from electrostatic discharge (ESD) events
- Assists equipment to pass IEC 61000-4-2, level 4 testing

FEATURES

- 0.25 pF (typ) Capacitance
- Low leakage current
- Low clamping voltage
- Fast response time (<1ns)
- Capable of withstanding numerous ESD strikes
- Compatible with standard reflow installation procedures
- Thick film technology
- Bi-directional protection



APPLICATIONS

Cellular phones

CAUTION: This device should not be used in Power Bus applications

MATERIALS INFORMATION

RoHS Compliant

Directive 2002/95/EC
Compliant


ELV Compliant

Directive 2000/53/EC
Compliant

Halogen Free*

HF

PART NUMBERING



* Halogen Free refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm

SUPERSEDED
NOT the LATEST
REVISION

TYPICAL DEVICE RATINGS AND CHARACTERISTICS

| | Continuous Max Operating Voltage | Typical TLP Trigger Voltage ¹ | Typical TLP Clamping Voltage ¹ after 30ns | Typical Capacitance ² , @ 1 MHz, 1V _{rms} | Typical Leakage Current @24V _{DC} | Max Leakage Current @24V _{DC} |
|--------|----------------------------------|--|--|---|--|--|
| Symbol | V_{DC} | $V_{T(TLP)}$ | $V_{C(TLP\ 30)}$ | C_p | $I_{L(Typ)}$ | $I_{L(MAX)}$ |
| Unit | V | V | V | pF | μA | μA |
| Value | 24 | 250 | 45 | 0.25 | <0.01 | 10.0 |

Note 1: TLP test method @ 1000V (refer to Fig. 5 on page 5)

Note 2: Typical capacitance @ 0V and 24V bias

GENERAL CHARACTERISTICS

Operating temperature: -55°C to +125°C

Storage temperature: -40°C to +85°C

ESD voltage capability (tested per IEC 61000-4-2)

- Contact discharge mode: 8kV (typ), 15kV (max)
- Air discharge mode: 15kV (typ), 25kV (max) [1 pulse: per customer request]

ESD pulse withstand: Typically 100 pulses (tested per IEC 61000-4-2, level 4, and contact method)

Environmental Specifications

| | Bias Humidity Test | Thermal Shock | Bias Heat Test | Bias Low Temp Test | Solderability | Solder Heat | Vibration | Mechanical Shock | Solvent Resistance |
|--------------------|--|--|---|---|------------------------------|--------------|---|--|--|
| Test Conditions | @ 85°C @ 85% RH V_{DC} (max) 1000 hours | -55°C to 125°C 30min dwell 1000 cycles | @ 125°C V_{DC} (max) 1000 hours | @ -55°C V_{DC} (max) 1000 hours | 250 °C +/- 5 °C 3s +/- 1s | 260 °C, 10s | 10 to 50Hz, 60s cycle, 2hrs each in X-Y-Z axis | 1500G, 0.5ms, X-Y-Z axis 3 times | IPA ultrasonic 300s |
| Pass/Fail Criteria | $I_L \leq 10\mu A$ | $I_L \leq 10\mu A$ | $I_L \leq 10\mu A$ | $I_L \leq 10\mu A$ | 95% coverage | 90% coverage | No Physical Damage $I_L \leq 10\mu A$ | No Physical Damage $I_L \leq 10\mu A$ | No Physical Damage $I_L \leq 10\mu A$ |

FIG 1: CAPACITANCE VS. FREQUENCY (TYPICAL SAMPLE)

(PESD1206Q Flat Response of Capacitance over Frequency Range)




FIG 2: EYE DIAGRAM (TYPICAL SAMPLE)

(PESD1206Q Eye Diagram Performance at 3.4 GHz)




FIG 3: INSERTION LOSS DIAGRAM (TYPICAL SAMPLE) (PESD1206Q Minimal Insertion Loss at 3.4 GHz)




FIG 4: ESD PROTECTION FOR HDMI





FIG 5: TYPICAL TRANSMISSION LINE PULSE RESPONSE GRAPH




ESD Protector Overvoltage Protection Device

Raychem Circuit Protection Products

PRODUCT: PESD1206Q-240

DOCUMENT: SCD 27553
REV LETTER: A
REV DATE: OCTOBER 9, 2008
PAGE NO.: 6 OF 9

DIMENSIONS




Drawing Not To Scale

| | Length A | | Height B | | End Terminal Width C | | Length Width D | | Length Width E | | Length Width F | |
|------|----------|---------|----------|---------|----------------------|---------|----------------|---------|----------------|---------|----------------|---------|
| | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| mm: | 3.1 | 3.3 | 0.4 | 0.6 | 0.1 | 0.3 | 1.5 | 1.7 | 0.2 | 0.6 | 0.2 | 0.6 |
| in*: | (0.122) | (0.130) | (0.016) | (0.024) | (0.004) | (0.012) | (0.059) | (0.067) | (0.008) | (0.024) | (0.008) | (0.024) |

* Round off approximation

RECOMMENDED LAND PATTERN:

Solder thickness 0.15 to 0.2mm




| | V | | W | | X | | Y | | Z | |
|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| mm: | 3.0 | 3.4 | 2.0 | 2.4 | 0.4 | 0.6 | 0.6 | 1.0 | 0.9 | 1.1 |
| in*: | (0.118) | (0.134) | (0.079) | (0.094) | (0.016) | (0.024) | (0.024) | (0.039) | (0.035) | (0.043) |

* Round off approximation

SOLDER REFLOW RECOMMENDATIONS:


| | | | |
|---|-----------------------|--|---|
| A | Temperature ramp up 1 | From ambient to Preheating temperature | 30s to 60s |
| B | Preheating | 140°C - 160°C | 60s to 120s |
| C | Temperature ramp up 2 | From Preheating to Main heating temperature | 20s to 40s |
| D | Main heating | at 200°C at 220°C at 240°C at 260°C | 60s ~ 70s 50s ~ 60s 30s ~ 40s 5s ~ 10s |
| E | Cooling | From main heating temperature to 100°C | max 4°C/s |



PACKAGING


| Packaging | Tape & Reel | Standard Box |
|---------------|-------------|--------------|
| PESD1206Q-240 | 5,000 | 25,000 |

EIA referenced Reel Dimensions for PESD Devices



Reel Dimensions (mm):

| | A | B | C | D | E | F | G |
|---------------------|------------|----------|-----------|-----------|-----------|----------|-----------|
| 1206 Devices | 178.0 ±2.0 | 2.0 ±0.5 | 13.0 ±0.5 | 21.0 ±0.8 | 62.0 ±1.5 | 9.0 ±0.5 | 13.0 ±1.0 |



Carrier Dimensions (mm):

| | A | B | C | D | E | F | L | W | T ¹ |
|---------------------|----------|-----------|-----------|-----------|----------|----------|------------|------------|----------------|
| 1206 Devices | 8.0 ±0.3 | 3.5 ±0.05 | 1.75 ±0.1 | 2.0 ±0.05 | 4.0 ±0.1 | 1.5 ±0.1 | 3.62 ±0.20 | 2.02 ±0.20 | 0.75 ±0.05 |

Note 1: Carrier thickness

Product Orientation – always face up (meaning the substrate is at the bottom), but parts do not have polarity mark.

POST REFLOW, CLEANING CONDITIONS

A 5% saponifier combined with water during wash.

For the ultrasonic process water temperature should be at 50°C and board should be submerged for a minimum of one minute in the solutions, then rinse and dry.

For in-line washing, the temperature of the water sprayed should be at 110°C, rinse and drying is done in-line.



WARNING

Warning: Application Limitations for PESD1206Q-240. This part is not intended to be used on power lines or for power bus applications. Users should independently evaluate the suitability of and test each product selected for their own applications

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of each product for their applications. Tyco Electronics reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product. This publication supersedes and replaces all information previously supplied. Without expressed or written consent by an officer of Tyco Electronics, Tyco Electronics does not authorize the use of any of its products as components in nuclear facility applications, aerospace, or in critical life support devices or systems. Tyco Electronics' only obligations are those in the Tyco Electronics Standard Terms and Conditions of Sale and in no case will Tyco Electronics be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

HDMI is a trademark of **HDMI Licensing LLC**

Bluetooth is a trademark of **Bluetooth SIG**

TE Logo and **Tyco Electronics** are trademarks