

"High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth Antenna

P/N 2450AT43B100

NEW with Ground Clearance Requirements Minimized

Detail Specification: 09/04/08

Page 1 of 4

General Specifications

Part Number	2450AT43B100
Frequency Range	2400 - 2500 Mhz
Peak Gain	1.3 dBi typ. (XZ-V)
Average Gain	-0.5 dBi typ. (XZ-V)
Return Loss	9.5 dB min.

Input Power	2W max.
Impedance	50 Ω
Reel Quantity	1,000
Operating Temperature	-40 to +85°C
Storage Temperature	+5 to +35°C, Humidity: 45-75%RH, 12 mos. Max



P/N	Packaging Style	Bulk	Suffix = S	Eg. 2450AT43B100S
		T & R	Suffix = E	Eg. 2450AT43B100E
Suffix	Termination Style	100% Tin	Suffix = None	Eg. 2450AT43B100(E or S)
		Tin / Lead	Please consult Factory	

Terminal Configuration

No.	Function
1	Feed Point
2	NC
3	NC
4	NC

Mechanical Dimensions

	In	mm
L	0.276 \pm 0.008	7.00 \pm 0.20
W	0.079 \pm 0.008	2.00 \pm 0.20
L1	0.102 \pm 0.008	2.60 \pm 0.20
W1	0.020 \pm 0.008	0.50 \pm 0.20
T	0.079 +.004/-0.008	2.00 +0.1/-0.2
a	0.020 \pm 0.012	0.50 \pm 0.30

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2008 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth Antenna

P/N 2450AT43B100

Detail Specification: 09/04/08

Page 2 of 4


Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

Line width should be designed to provide 50Ω impedance matching characteristics.

* Note: Pins 3 & 4, although "NC", must be soldered to its PCB pads for proper electrical operation

With Matching Circuits



(Matching circuit and component values will be different, depending on PCB layout)

JTI P/N for Matching Circuit:
Inductor (2.2nH): L-07C2N2SV6T
Inductor (2.7nH): L-07C2N7SV6T

"High Frequency Ceramic Solutions"


2.4 GHz WLAN, Home RF, Bluetooth Antenna

P/N 2450AT43B100

Detail Specification: 09/04/08

Page 3 of 4

Typical Electrical Characteristics (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2008 Johanson Technology, Inc. All Rights Reserved


"High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth Antenna

P/N 2450AT43B100

Detail Specification: 09/04/08

Page 4 of 4



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2008 Johanson Technology, Inc. All Rights Reserved